

Network Video Recorder

NVR304-S-P Series



Key Features

- Support Ultra265/H.265/H.264 video formats
- 16/32-channel input
- Plug & Play with 16 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- Support HDMI and VGA simultaneous output
- Up to 8 Megapixels resolution recording
- 4 SATA HDDs, up to 10TB for each HDD
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade


Specifications

Model	NVR304-16S-P16		NVR304-32S-P16	
Video/Audio Input				
IP Video Input	16-ch		32-ch	
Two-way Audio Input	1-ch, RCA			
Network				
Incoming Bandwidth	160Mbps			
Outgoing Bandwidth	64Mbps			
Remote Users	128			
Protocols	P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, SMTP, NTP, SNMP, RTSP, IPv4, IPv6, ONVIF			
Video/Audio Output				
HDMI/VGA Output	HDMI: 4K (3840x2160@30), 1920X1080@60, 1920X1080@50, 1600X1200@60, 1280X1024@60, 1280X720@60, 1024X768@60 VGA: 1920X1080@60, 1920X1080@50, 1280X1024@60, 1280X720@60, 1024X768@60			
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF			
Audio Output	1-ch, RCA			
Synchronous Playback	16-ch		32-ch	
Corridor Mode Screen	3/4/5/7/9/10/12/16		3/4/5/7/9/10/12/16/32	
Decoding				
Decoding format	Ultra265/H.265/H.264			
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF			
Capability	2 x 4K@30, 4x 4MP@30, 5 x 3MP@30, 8 x 1080P@30, 16 x 720P@30		2 x 4K@30, 4x 4MP@30, 5 x 3MP@30, 8 x 1080P@30, 16 x 720P@30, 32 x D1@30	
Hard Disk				
SATA	4 SATA interfaces			
Capacity	Up to 10TB for each disk			
Smart				
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed			
VCA Search	Face search, Behavior search			
Statistical Analysis	People counting			
External Interface				
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface			
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0			
Serial Interface	1 x RS485			
Alarm In	16-ch			
Alarm Out	4-ch			
PoE				
Interface	16 RJ-45 10M/100M self-adaptive Ethernet Interface			
Max Power	Max 30W for single port Max 240W in total			
Supported Standard	IEEE 802.3af/at			

General


Power Supply	100 ~ 240 V AC Power Consumption: ≤15W(without HDD)
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	400mm ×362mm × 74mm (15.7" × 14.2" ×2.9")
Weight (without HDD)	≤5kg (5.29lb)

Dimensions



Rear Panel

Take **NVR304-16S-P16** for example



Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://sgcdn.uniview.com>

©2020 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

* Product specifications and availability are subject to change without notice.