

# SC10-203-4H(6mm)

## Key Features

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 6 mm fixed focal lens
- True Day/Night
- EXIR 2.0, up to 40 m IR distance
- IP66
- Switchable TVI/AHD/CVI/CVBS



## Specification

Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Effective Pixels	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/30,000 s NTSC: 1/30 s to 1/50,000 s
Lens	6 mm fixed focal lens
Horizontal Field of View	103° (2.8 mm), 82.2° (3.6 mm), 54° (6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotate: 0° to 360°
Synchronization	Internal synchronization
S/N Ratio	> 62 dB
Interface	
Video Output	1 HD analog output/1 Vp-p composite output (75Ω/BNC)
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 15%
Power Consumption	Max. 4 W
Ingress Protection	IP66
Material	Metal & Plastic
IR Range	Up to 20 m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	86.7 mm × 81.6 mm × 226 mm (3.4" × 3.2" × 8.9")
Weight	Approx. 430 g (0.95 lb)

## Dimension

